

Product	Description	Operating System																
		DOS	Win 3.x	Win NT4	Win 95	Win 98	Win 98SE	Win Me	Win 2000	Win XP	Win XP 64	Win Server 2003	Linux 2.4+	Mac 8.6+	QNX 6.2	THEOS	SCO 5.07	SCO 6.0
Serial PCI																		
SSerial-PCI	One 9-pin port, 16550 UART	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
SSerial-PCI/LP	One 25-pin port, 16550 UART, low-profile	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
RS422 SS-PCI	One 9-pin port, 16550 UART, RS-422 pinout	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
LavaPort-650	One 9-pin port, 16650 UART			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
DSerial-PCI	Two 9-pin ports, 16550 UARTs	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
DSerial-PCI/LP	Two 9-pin ports, 16550 UARTs, low-profile	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
DSerial-PCI 3.3V	Two 9-pin ports, 16550 UARTs, for 3.3 volt PCI, PCI-X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
DSerial-PCI Powered	Two 9-pin ports, 16550 UARTs, 5 & 12 VDC powered serial ports	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
DSerial-PCI OS/2 Ready	Two 9-pin ports, 16550 UARTs	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
LavaPort-PCI	Two 9-pin ports, 16650 UARTs			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Quattro-PCI	Four 9-pin ports, 16550 UARTs			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Quattro-PCI 3.3V	Four 9-pin ports, 16550 UARTs, for 3.3 volt PCI, PCI-X			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Quattro-PCI/LP	Four 9-pin ports, 16550 UARTs, low profile			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Quattro-PCI Powered	Four 9-pin ports, 16550 UARTs, 5 & 12 VDC powered serial ports			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
LavaPort-Quad	Four 9-pin ports, 16650 UARTs			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Octopus-550	Eight 9-pin ports, 16550 UARTs			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Serial ISA																		
SSerial-550	One 25-pin port, COM 1-4, 16550 UART	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
LavaPort-ISA	One 9-pin port, COM 1-4, 16650 UART			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
LavaPort-PnP	One 9-pin port, Plug and Play, 16650 UART				✓	✓	✓	✓	✓									?
DSerial-550	Two 9-pin ports, COM 1-6, 16550 UARTs	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
RS422-550	Two 9-pin ports, 16550 UARTs, RS-422 pinouts	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Combo PCI Boards																		
SP-PCI	One 9-pin serial, 16550 UART, one 25-pin bi-dir. parallel port	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Legend: ✓ = driver support; ◆ = supported in some port modes																		
Rev. A01 LAVA Computer MFG Inc. 2 Vulcan Street, Toronto, ON Canada M9W 1L2 Tel: +416.674-5942 Fax: +416.674-8262 www.lavalink.com																		

Product	Description	Operating System																
		DOS	Win 3.x	Win NT4	Win 95	Win 98	Win 98SE	Win Me	Win 2000	Win XP	Win XP 64	Win Server 2003	Linux 2.4+	Mac 8.6+	QNX 6.2	THEOS	SCO 5.07	SCO 6.0
2SP-PCI	Two serial (9 & 25 pin), 16550 UARTs, one 25-pin EPP parallel port	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
2SP-PCI Powered	Two serial (9 & 25 pin), 16550 UARTs, one 25-pin EPP parallel port, 5 & 12 VDC powered serial ports	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
LavaPort-Plus	Two serial (9 & 25 pin), 16650 UARTs, one 25-pin EPP parallel port			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Combo ISA Board																		
2SP-ISA	Two serial ports (9 & 25 pin), 16550 UARTs, IRQ2/3/4/5/10/11/12/15, COM 1-4; one 25-pin bi-dir. parallel port, LPT 1-2, IRQ 5/7	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Parallel PCI I/O Boards																		
Parallel-PCI	One 25-pin Enhanced Parallel Port (EPP)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Parallel-PCI 3.3V	One 25-pin Enhanced Parallel Port (EPP), for 3.3 volt PCI & PCI-X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Dual Parallel-PCI	Two 25-pin Enhanced Parallel Ports (EPPs)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Parallel-PCI/LP	One 25-pin Enhanced Parallel Port (EPP), low-profile	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Parallel ISA I/O Boards																		
Parallel Bi-directional	One 25-pin, 8-bit bi-dir. port,LPT 1-3, IRQ 5/7/none	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Parallel-ECP/EPP	One 25-pin Extended Capabilities Port/ Enhanced Parallel Port, LPT 1-6, IRQ 2/3/4/5/7/10/11/12	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	?
Ether-Serial																		
ESL 1-232-DB9	RS-232, 9-pin DB-9	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 1-232-RJ45	RS-232, 10-wire RJ-45	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 1-422-DB9	RS-422, 9-pin DB-9	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 1-422-RJ45	RS-422, 10-wire RJ-45	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 2-232-DB9	RS-232, 9-pin DB-9s	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 2-232-RJ45	RS-232, 10-wire RJ-45s	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 2-422-DB9	RS-422, 9-pin DB-9s	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 2-422-RJ45	RS-422, 10-wire RJ-45s	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 4-232-DB9	RS-232, 9-pin DB-9s	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 4-232-DB9-CBL	RS-232, 9-pin DB-9s with fan-out cable	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆

Legend: ✓ = driver support; ◆ = supported in some port modes

Product	Description	Operating System																
		DOS	Win 3.x	Win NT4	Win 95	Win 98	Win 98SE	Win Me	Win 2000	Win XP	Win XP 64	Win Server 2003	Linux 2.4+	Mac 8.6+	QNX 6.2	THEOS	SCO 5.07	SCO 6.0
ESL 4-232-RJ45	RS-232, 10-wire RJ-45s	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 5-232-DB9-EMB	RS-232, 9-pin DB9s, for embedded applicatons	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 8-232-DB9-CBL	RS-232, 9-pin DB-9s with fan-out cables	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
ESL 8-232-RJ45	RS-232, 10-wire RJ-45s	◆	◆	✓	✓	✓	✓	✓	✓	✓	◆	✓	✓	◆	✓		◆	◆
PayLink																		
PayLink-IP/Dial	Single RJ-11 POTS port, 10 Base-T Ethernet, 128-bit SSL 3.0 encryption	◆	◆	✓	✓	✓	✓	✓	✓	✓		✓	✓		◆		◆	◆
PayLink-IP/232	Single RS-232 DB-9 serial port, 10 Base-T Ethernet, 128-bit SSL 3.0 encryption	◆	◆	✓	✓	✓	✓	✓	✓	✓		✓	✓		◆		◆	◆
DataTap																		
DataTap-IP	Dual RS-232 DB-9 serial ports, 10 Base-T Ethernet	◆	◆	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓		◆	◆
USB 1.1 and 2.0																		
USB 1.1 Host Adapter	Dual USB 1.1 ports, 12 Mbps						✓	✓	✓	✓	✓		✓	✓				?
USB 2.0 Host Adapter	Dual USB 2.0 ports, 480 Mbps								✓	✓	✓		✓					?
IEEE 1394 (FireWire)																		
IEEE 1394 FireHost	Dual IEEE 1394 ports, 400 Mbps						✓	✓	✓	✓	✓		✓	✓				?
IEEE 1394-IDE Controller	FireWire - IDE interface board						✓	✓	✓	✓			✓					?
Specialty																		
8255-PIO	PCI to 8255 PIO interface board				✓	✓	✓	✓	✓	✓								?
Discontinued																		
SPH-USB 1.1 Hub	Three powered USB 1.1, bi-dir. parallel port, 16550 serial port						✓	✓	✓	✓				✓				?
Kazan	Hard drive enclosure with USB 2.0 - IDE interface	✓					✓	✓	✓	✓			✓	✓				?
FireDrive	Hard drive enclosure with FireWire - IDE interface						✓	✓	✓	✓			✓					?

Legend: ✓ = driver support; ◆ = supported in some port modes